



PAKISTAN STATE OIL

PSO DIESELUBE

Diesel Engine Oil

PRODUCT DESCRIPTION

PSO Dieselube HD 50 is a high performance and high detergency lubricant especially developed to meet the stringent requirements of diesel engines where API CD/SE oil is recommended.

APPLICATIONS

- Suitable for applications requiring performance level of API classification CD/SE.
- Appropriate choice for a wide variety of diesel engine vehicles for agricultural and off-road applications.
- Suitable to use in heavy and light commercial vehicles.

PERFORMANCE STANDARD

The superior additive technology used in the formulation of PSO DIESELUBE HD 50 endorses the following performance standard:

API CD/SE

BENEFITS

- Effective control of engine wear and deposits on engine parts.
- An economical product with good all-round performance.
- Protects against rust and corrosion.

PRODUCT CHARACTERISTICS*

PROPERTIES	METHOD	TYPICAL RESULTS - 50
Density @ 15 °C, Kg/liter	ASTM D-4052	0.9252
Kinematic Viscosity @100 °C, cSt	ASTM D-445	19.87
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	250.5
Viscosity Index	ASTM D-2270	91
Flash Point (COC), °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-6
Total Base Number, mg KOH/g	ASTM D-2896	9.1

* These typical characteristics mentioned are based on current mean values.



HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from PSO representative.



ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



ADVICE

Advice on application not covered in this leaflet, may be obtained from PSO representative.