



PRODUCT DESCRIPTION

PSO Two-stroke Oil is a cost-effective quality oil for two-stroke engines, especially developed for small to medium size air-cooled two-stroke engines used in motor cycles, scooters and three-wheel light passenger vehicles. PSO Two-stroke Oil is formulated with an up-graded low ash additive system to ensure protection against scuffing of piston rings and liner wear by minimizing piston ring deposits.

APPLICATIONS

- Developed for the lubrication of all makes of Two-stroke automotive gasoline engines.
- Three-wheel light passenger vehicles powered by two-stroke engine.
- Chainsaws and portable equipment powered by two-stroke engines.

PERFORMANCE STANDARDS

The superior additive technology used in the formulation of PSO Two-stroke Oil endorses the following performance standards:

- JASO FB
- ISO L-EGB

BENEFITS

- Excellent thermal stability supports high temperature application in air-cooled engines.
- Protection against ring shaking and exhaust blocking.
- Control of engine deposits to prevent pre-ignition.
- Consistent power output.
- Longer engine service life.
- Mixed at fuel to oil ratio recommended by the equipment manufacturer.

PRODUCT CHARACTERISTICS*

PROPERTIES	Method	TYPICAL RESULTS
Density @ 15 °C, Kg/liter	ASTM D-4052	0.8785
Kinematic Viscosity @100 °C, cSt	ASTM D-445	10.3
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	80.3
Viscosity Index	ASTM D-2270	100
Flash Point (COC), °C	ASTM D-92	140

* These typical characteristics mentioned are based on current mean values



HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from PSO representative.



ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



ADVICE

Advice on application not covered in this leaflet, may be obtained from PSO representative.