



Pakistan State Oil

MATERIAL SAFETY DATA SHEET

PSO TEXOL

1. Identification of the substance/preparation and of the company / undertaking

Product name	PSO TEXOL 22, 32, 46, 68, 100, 150, 220, 320, 460 & 680
MSDS #	08-03
Product Use	Non-additive containing lubricant for circulatory systems For specific application advice see appropriate Technical Data Sheet or consult your PSO representative.
Supplier	Lubricants Technology Pakistan State Oil Co. Ltd. 7 th Floor, PSO House Khayaban-e-Iqbal, Clifton, Karachi, Pakistan. Tel. 92 21 99203866
EMERGENCY TELEPHONE NUMBER	+92 21 99203753

2. Composition/information on ingredients

- Highly refined mineral oil (IP 346 DMSO extract < 3%).
- This product does not contain any hazardous ingredients at or above regulated thresholds.

3. Hazards identification

- This material is not considered to be hazardous, but should be handled in accordance with good industrial hygiene and safety practices.
- Note: High Pressure Applications
- Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
- See 'Medical Advice' under First-Aid Measures, Section 4 of this Safety Data Sheet.

4. First-aid measures

Eyes

- Wash eye thoroughly with copious quantities of water, ensuring eyelids are held open. Obtain medical advice if any pain or redness develops or persists.

Skin

- Wash skin thoroughly with soap and water as soon as reasonably practicable. Remove heavily contaminated clothing and wash underlying skin.

Ingestion

- If contamination of the mouth occurs, wash out thoroughly with water. Except as a deliberate act, the ingestion of large amounts of product is unlikely. If it should occur, do not induce vomiting; obtain medical advice

Inhalation

- If inhalation of mists, fumes or vapor causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist obtain medical advice.

Medical Advice

- Treatment should in general be symptomatic and directed to relieving any effects.
- Note: High Pressure Applications
- Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
- Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.



MATERIAL SAFETY DATA SHEET

Pakistan State Oil

- Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

5. Fire-fighting measures

- Use foam, dry powder or water fog. DO NOT USE water jets.
- Fires in confined spaces should be dealt with by trained personnel wearing approved breathing apparatus.
- Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over.

Combustion Products

- Toxic fumes may be evolved on burning or exposure to heat.
- See Stability and Reactivity, Section 10 of this Safety Data Sheet.

6. Accidental release measures

- Contain and recover spilled material using sand or other suitable inert absorbent material.
- It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage, which may be reasonably anticipated.
- Spilled material may make surfaces slippery.
- Protect drains from potential spills to minimize contamination. Do not wash product into drainage system.
- In the case of large spills contact the appropriate authorities.
- In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies.

7. Handling and storage

Handling Precautions

- Avoid contact with eyes. If splashing is likely to occur wear a full face visor or chemical goggles as appropriate.
- Avoid frequent or prolonged skin contact with fresh or used product.
- Good working practices, high standards of personal hygiene and plant cleanliness must be maintained at all times.
- Wash hands thoroughly after contact.
- Use disposable cloths and discard when soiled. Do not put soiled cloths into pockets.

Fire Prevention

- Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Storage Conditions

- Store under cover away from heat and sources of ignition.

8. Exposure controls/personal protection

Exposure Limits

- There is no appropriate occupational exposure limit for this material.
- Ensure good ventilation.
- Avoid, as far as reasonably practicable, inhalation of vapor, mists or fumes generated during use.
- If vapor, mists or fumes are generated, their concentration in the workplace air should be controlled to the lowest reasonably practicable level.

Protective Clothing

- Wear face visor or goggles in circumstances where eye contact can accidentally occur.
- If skin contact is likely, wear impervious protective clothing and/or gloves.
- Protective clothing should be regularly dry cleaned. Change heavily contaminated clothing as soon as reasonably practicable; dry clean, launder and preferably starch before re-use. Wash any contaminated underlying skin with soap and water.

Respiratory Protection

- Respiratory protection is unnecessary, provided the concentration of vapor, mists or fumes is adequately controlled.
- The use of respiratory equipment must be strictly in accordance with the manufacturers' instructions and any statutory requirements governing its selection and use.



MATERIAL SAFETY DATA SHEET

Pakistan State Oil

9. Physical and chemical properties

Typical Values_

Grades:	32	46	68	100	150	220	320	460	680
Test Method Units									
Physical state	liquid	liquid	liquid	liquid	liquid	liquid	liquid	liquid	liquid
Color	amber	amber	amber	amber	amber	amber	amber	amber	amber
Odor	oily	oily	oily	oily	oily	oily	oily	oily	oily
Kinematic viscosity @ 40°C ASTM D 445 mm ² /s	32	46	68	100	150	220	320	460	650
Flash point (COC) ASTM D 92 °C	190	200	220	230	240	250	260	270	280
Pour point ASTM D 97 °C	-6	-9	-9	-9	-6	-6	-6	-3	-3

10. STABILITY AND REACTIVITY

- Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use.
- Hazardous polymerization reactions will not occur.
- This material is combustible.

Materials to Avoid

- Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products

- Thermal decomposition products will vary with conditions.
- Incomplete combustion will generate smoke, carbon dioxide and hazardous gases, including carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Eyes

- Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Skin

- Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.

Ingestion

- Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhea.

Inhalation

- At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility.
- May cause irritation to eyes, nose and throat due to exposure to vapor, mists or fumes.
- May be harmful by inhalation if exposure to vapor, mists or fumes resulting from thermal decomposition products occurs.

12. ECOLOGICAL INFORMATION

Mobility

- Spillages may penetrate the soil causing ground water contamination.

Persistence and degradability

- This product is inherently biodegradable.

Bio-accumulative potential

- There is no evidence to suggest bioaccumulation will occur.

Aquatic toxicity

- Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13. DISPOSAL CONSIDERATIONS

- Where possible, arrange for product to be recycled.
- Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.
- Incineration may be carried out under controlled conditions provided that local regulations for emissions are met.



Pakistan State Oil

MATERIAL SAFETY DATA SHEET

14. TRANSPORT INFORMATION

- Not classified as hazardous for transport (ADR, RID, UN, IMO, and IATA/ICAO).
-

15. REGULATORY INFORMATION

- Not classified as hazardous for supply.
-

16. OTHER INFORMATION

Compiled by:

Lubricants Technology
7th Floor, Khayaban-e-Iqbal
Karachi

This data sheet and the health, safety and environmental information it contains are considered to be accurate as of the date specified below. We have reviewed any information contained herein, which we received from sources outside the PSO. However, no warranty or representation, express or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. PSO shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards