



GENERATOR OIL

Improved Technology

PSO Generator Oil is specially formulated to meet the lubrication requirements of leading manufacturers of portable generators. The synergy of selective additive technology and high viscosity index base oils provides excellent protection to engine components operating at extreme temperatures and load conditions for longer period.

Benefits

- Instant lubrication and easy cranking at start-up.
- Gives extra protection at high operating temperatures.
- Improved anti-wear property and resists against engine deposits.
- Equally suitable for both gasoline and CNG fuelled generators.
- Improved protection against rust and corrosion.

Applications

- Recommended for use in a wide variety of portable domestic and commercially used generators.
- Formulated at SAE 20W-40 viscosity grade for gasoline and natural gas engines in local environment, where API SG/CD is recommended.

Performance Standard

- API SG/CD

Typical Characteristics*

PROPERTIES	METHODS	TYPICAL RESULTS
		20W-40
Density @ 15°C, kg/L	ASTM D-4052	0.8915
K.Viscosity @ 100°C, cSt	ASTM D-445	14.30
K.Viscosity @ 40°C, cSt	ASTM D-445	116.20
Viscosity Index	ASTM D-2270	124
Flash Point (COC), °C	ASTM D-92	220
Pour Point, °C	ASTM D-97	-21
Total Base Number, mg KOH/g	ASTM D-2896	6

*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from lubricants.technical@psopk.com